Massachusetts Fire Training Council Firefighter Practical Certification Examination

NFPA Objective: 5.3.1 (B) Minimum to pass 13				
PERFORMANCE: 1. All Personal Protective Equipment (PPE) is properly worn. 2. Obtain a full air cylinder. (90% or above-2216 psi=1944/4500 psi=4050) 3. Disconnect facepiece from the regulator. 4. Close the cylinder valve on the used bottle. 5. Release pressure from high-pressure hoseline through regulator system and not by disconnecting high pressure hoseline from empty cylinder. 6. Once all pressure is released, disconnect high-pressure hoseline from empty cylinder. 7. Release cylinder clamps. 8. Remove used cylinder. 9. Check replacement cylinder opening for debris. Open cylinder valve to clear debris if necessary.	Skill Title: SCBA CYLINDER REPLACEMENT-ONE FIREFIGHTER METHOD			
PERFORMANCE: 1. All Personal Protective Equipment (PPE) is properly worn. 2. Obtain a full air cylinder. (90% or above-2216 psi=1944/4500 psi=4050) 3. Disconnect facepiece from the regulator. 4. Close the cylinder valve on the used bottle. 5. Release pressure from high-pressure hoseline through regulator system and not by disconnecting high pressure hoseline from empty cylinder. 6. Once all pressure is released, disconnect high-pressure hoseline from empty cylinder. 7. Release cylinder clamps. 8. Remove used cylinder. 9. Check replacement cylinder opening for debris. Open cylinder valve to clear debris if necessary.	NFPA Objective: 5.3.1 (B) Minimum to pass 13			
 Obtain a full air cylinder. (90% or above-2216 psi=1944/4500 psi=4050) Disconnect facepiece from the regulator. Close the cylinder valve on the used bottle. Release pressure from high-pressure hoseline through regulator system and not by disconnecting high pressure hoseline from empty cylinder. Once all pressure is released, disconnect high-pressure hoseline from empty cylinder. Release cylinder clamps. Remove used cylinder. Check replacement cylinder opening for debris. Open cylinder valve to clear debris if necessary. 	F			
 Obtain a full air cylinder. (90% or above-2216 psi=1944/4500 psi=4050) Disconnect facepiece from the regulator. Close the cylinder valve on the used bottle. Release pressure from high-pressure hoseline through regulator system and not by disconnecting high pressure hoseline from empty cylinder. Once all pressure is released, disconnect high-pressure hoseline from empty cylinder. Release cylinder clamps. Remove used cylinder. Check replacement cylinder opening for debris. Open cylinder valve to clear debris if necessary. 				
3. Disconnect facepiece from the regulator. 4. Close the cylinder valve on the used bottle. 5. Release pressure from high-pressure hoseline through regulator system and not by disconnecting high pressure hoseline from empty cylinder. 6. Once all pressure is released, disconnect high-pressure hoseline from empty cylinder. 7. Release cylinder clamps. 8. Remove used cylinder. 9. Check replacement cylinder opening for debris. Open cylinder valve to clear debris if necessary.				
 Close the cylinder valve on the used bottle. Release pressure from high-pressure hoseline through regulator system and not by disconnecting high pressure hoseline from empty cylinder. Once all pressure is released, disconnect high-pressure hoseline from empty cylinder. Release cylinder clamps. Remove used cylinder. Check replacement cylinder opening for debris. Open cylinder valve to clear debris if necessary. 				
 Release pressure from high-pressure hoseline through regulator system and not by disconnecting high pressure hoseline from empty cylinder. Once all pressure is released, disconnect high-pressure hoseline from empty cylinder. Release cylinder clamps. Remove used cylinder. Check replacement cylinder opening for debris. Open cylinder valve to clear debris if necessary. 				
not by disconnecting high pressure hoseline from empty cylinder. 6. Once all pressure is released, disconnect high-pressure hoseline from empty cylinder. 7. Release cylinder clamps. 8. Remove used cylinder. 9. Check replacement cylinder opening for debris. Open cylinder valve to clear debris if necessary.				
6. Once all pressure is released, disconnect high-pressure hoseline from empty cylinder. 7. Release cylinder clamps. 8. Remove used cylinder. 9. Check replacement cylinder opening for debris. Open cylinder valve to clear debris if necessary.				
cylinder. 7. Release cylinder clamps. 8. Remove used cylinder. 9. Check replacement cylinder opening for debris. Open cylinder valve to clear debris if necessary.				
7. Release cylinder clamps. 8. Remove used cylinder. 9. Check replacement cylinder opening for debris. Open cylinder valve to clear debris if necessary.				
8. Remove used cylinder. 9. Check replacement cylinder opening for debris. Open cylinder valve to clear debris if necessary.				
9. Check replacement cylinder opening for debris. Open cylinder valve to clear debris if necessary.				
clear debris if necessary.				
10. Check high-pi essui e nosenne connection O"i hig foi mitegi ity.				
11. Install replacement cylinder into harness.				
2. Connect high-pressure hoseline connection hand tight.				
3. Adjust cylinder in harness and secure clamps.				
4. Open cylinder valve and check regulator gauge.				
(Difference between cylinder and regulator gauge shall not exceed 100 psi)				
15. Close cylinder valve.				
16. Release all pressure through regulator system.				
17. Place unit back in service.				

Failure of this critical port	ion is cause for entire skill failure
Examiner Signature	